

TUBULATIONS AND SPECIALIZED TUBING TOOLS

Bulged Stainless Steel Tubulations

Scanivalve manufactures a complete line of bulged stainless steel tubulations. The tubing is bulged on one end to insure leak tight connections. Scanivalve's plastic tubing and the brass or stainless steel helical tubing clamps fit over this bulge. The customer should epoxy the nonbulged end into his equipment. The tubulations are manufactured to lengths between .55 inches and 8.0 inches.



To order, specify:		
ScanCo #	Standard Lengths-Inches	Tubulation Size
TUBN-040 (Specify Length)	.55, .75, 1.0, 2.0, 3.0, 4.0, 6.0, 8.0	.040 Inch (1.02mm) O.D.
TUBN-063 (Specify Length)	.56, .75, 1.0, 2.0, 3.0, 4.0, 6.0, 8.0	.063 Inch (1.59mm) O.D.
TUBN-125 (Specify Length)	.75, 1.0, 2.0, 3.0, 4.0, 6.0, 8.0	.125 Inch (3.18mm) O.D.

Tubing Push-on Tool

This tool is designed for use with vinyl, nylon, Teflon and urethane tubing. The tool is used by grasping the tubing adjacent to the clamp (after the clamp has been screwed onto the tubing) and pushing it onto our standard stainless steel tubulations. It can also be used to push on tubing without clamps.



To order, specify ScanCo #	
TPOTL-040	
TPOTL-063	
TPOTL-125	
TPOTL-125 HW	

Model Tubulation Size

